

Nuffield and Leyland Tractor Brief Specification and Features - 1948 to 1982

Model & Year	Engine type	Cylinders and Capacity in litres	Power & Torque	Transmission	Hydraulics	Comments	Notes	
3/42 1961 to 64	BMC OEG Diesel 28T/TA/TD	3 - 2.8	39.8 bhp 118 lbf ft @ 1600 rpm	5 forward + 1 reverse	2000 psi 2830 lb lift Cat 1 & 2 linkage	1. Pedal operated Diff lock std 2. All tractors built at Bathgate in Scotland from 1962	I.P.T.O. Std on Deluxe Models	
4/60 1961 to 64	BMC OEE Diesel 38T/TA/TD	4 - 3.77	57.5 bhp 168 lbf ft @ 1250 rpm			1. Optional PAS		
10/42 1964 to 67	BMC Diesel 28T/TA/TD	3 - 2.8	42.7 bhp 127 lbf ft @ 1350 rpm	10 forward + 2 reverse	Hydraulics standard with draught control and single acting top link	1. Self energising independent dry disc brakes 2. Optional PAS 3. Mechanical Injection Pump governor introduced		
10/60 1964 to 67	BMC Diesel 38T/TA/TD	4 - 3.77	57.5 bhp 170 lbf ft @ 1250 rpm	High/Low gears added				
Mini 1965 to 68	BMC 'A' Series Diesel	4 - 950cc	15 bhp 38 lbf ft @ 1750 rpm	9 forward + 3 reverse Constant Mesh with sliding collar	2500 psi 1000 lb lift	1. Monocoque con- struction 2. Three pedal self energising dry disc brakes 3. Hand operated diff lock and single clutch		Standard 2 speed PTO - 540/1000 rpm
Mini 1967 to 68	BMC 'A' Series Petrol	4 - 950cc	20 bhp 40 lbf ft @ 1650 rpm					